



VP8800

PCI 5.X COUNTERTOP PAYMENT TERMINAL

The VP8800 is a Contactless/NFC and Magstripe payment device with a crisp 3.5" color LCD for signature and touch navigation all wrapped up in an eye-catching industrial design, making it the ideal solution for countertop environments. The VP8800 simplifies integration with a proven common EMV L2 kernel. It is a stunning payment solution that can be run in either a fully or semi integrated payment mode supporting all major payment brands, as well as the latest mobile wallets and loyalty programs/schemes.



COMMON KERNEL, UNCOMMONLY SIMPLE.

The ViVOPay VP8800 is an EMV Contact, Contactless/NFC and MagStripe PINpad payment solution ideally suited for countertop environments. Ask us how our common kernel can speed up your time to market and save you costly L3 approvals!

CONTACT US TODAY!

CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
FAX: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

CANADA

(714) 761-6368
CANADA@IDTECHPRODUCTS.COM

SOUTH AMERICA

+55-11-3079-2255
INTERNATIONALSALLES@
IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA
EMEA@IDTECHPRODUCTS.COM

VP8800 SPECS

PROCESSOR	ARM A7 32-Bit 528 MHz
MEMORY	128 MB RAM + 64 MB Flash, Micro SD of 32GB
DISPLAY	3.5" 320x480 HVGA Signature capable capacitive touch screen
MAGNETIC CARD READER	3 track bi-directional 1,000,000 swipes
SMART CARD READER	Smart Card 500,000 insertions EMV Level 1 & Level 2 certified (ID TECH Common Kernel)
CONTACTLESS CARD READER	ISO14443 A&B, MiFare, ISO18092-capable, VISA VCPS, MasterCard MCL, AMEX Expresspay, Discover DPAS, Interac Flash, Apple Pay & VAS, Google Pay & SmartTap, Samsung Pay, UPI
SAM SLOTS	3 SAMS
KEYPAD	Backlit 15 Keys with raised symbols
PCI	5.x
CONNECTIVITY	USB HID, RS-232, Ethernet
DIMENSIONS	189mm x 96mm x 58mm
WEIGHT	400g (~14 ounces)
AUDIO FEEDBACK	Buzzer
OPERATING TEMP	0 to 55° C (32 to 131° F)
STORAGE	-25 to 65° C (-13 to 149° F)
HUMIDITY	10 to 90% non-condensing
VOLTAGE	5 VDC regulated, +/- 10% Consumption 6 W maximum

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

